Patent

NASA Case No.: NPO-20821-1-CU

## IN THE CLAIMS

Please insert the following claims in place of the currently pending claims:

- 1-2. (Canceled).
- (Currently Amended) A solid-state scanning microscope, comprising:
   a source of collimated radiant energy:
- a plurality of narrow angle filters comprising a microchannel structure to permit the passage of only unscattered radiant energy through the microchannels, the microchannel structure having a first end and a second end;
- a solid-state sensing array comprising a plurality of sensing elements, attached at the first end of the microchannel structure, the sensing elements being sensitive to radiant energy, a plurality of the microchannels being aligned each to correspond with an individual sensor element of the solid-state sensing array;
- a planar member of an optically conductive material suitable for conducting radiant energy, the planar member having a first side and a second side, the first side of the planar member being placed perpendicular to the second end of the microchannel structure and attached to the microchannel structure allowing for an air-gap between the planar member and the microchannel structure;
- an index matching fluid placed adjacent to the second side of the planar member, the index matching fluid being matched to the index of the planar member, the index matching fluid continuously filling the region between the surface of the <u>a</u> sample and the second side of the planar member; and

08/08/2005 09:44 FAX 818 393 3160

Patent

NASA Case No.: NPO-20821-1-CU

a prism placed upon the planar member so as to conduct the source of radiant energy operatively into the planar member, the radiant energy being reflected by the first side and not reflected by the second side of the planar member, the radiant energy escaping the second side of the planar member to illuminate the surface of the sample, some portion of the radiant energy being reflected by the sample to enter the microchannels, that portion of the radiant energy entering the microchannels that is parallel to the microchannel walls travels to the solid-state sensing elements to generate electrical signals that can enable an image to be reconstructed by an external device.

- (Original) The solid-state scanning microscope of Claim 3, wherein the radiant energy is laser light radiation.
- (Original) The solid-state scanning microscope of Claim 3,
   wherein the radiant energy is visible light radiation.
- (Original) The solid-state scanning microscope of Claim 3,
   wherein the source of radiant energy is a solid-state emitter.
- 7. (Currently Amended) A solid-state scanning microscope, comprising:

a plurality of narrow angle filters comprising a microchannel structure to permit the passage of only unscattered radiant energy through the microchannels, the microchannel structure having a first end and a second end;

a solid-state sensing array comprising a plurality of sensing elements, attached at the first end of the microchannel structure, a plurality of the microchannels being aligned each to correspond with an individual sensing element of the sensing array;

Patent

NASA Case No.: NPO-20821-1-CU

a plurality of solid-state emitters for emitting radiant energy mounted on the second end of the microchannel structure, comprising a size and a mounting location to prevent unreflected light from entering the microchannels, the emitters illuminating the surface of a sample, some portion of the radiant energy being reflected by the sample to enter the microchannels, that portion of the radiant energy entering the microchannels that is parallel to the microchannel walls travels to the sensing elements to generate electrical signals that can enable an image to be reconstructed by an external device; and

a transparent planar member adjacent to the second end of the microchannel structure, the transparent covering containing conduction paths to conduct power to the solid-state emitters, the transparent cover protecting the second end of the microchannel structure from damage and preventing the entrance of foreign objects into the microchannels.

- (Original) The solid-state scanning microscope of Claim 7,
   wherein the solid-state emitters are Light Emitting Diodes.
- (Original) The solid-state scanning microscope of Claim 7,
   wherein the solid-state emitters are Light Emitting Polymers.

10-14. (Cancelled)

- 15. (Currently Amended) A solid-state scanning microscope, comprising:
- a scanning stage for providing structural support for moving the microscope, the scanning stage having a first side and a second side;
- a solid-state emitter for radiating energy, the emitter having a first side and a second side, the first side of the emitter radiating energy, the second side of the emitter mounted to the first side of the scanning stage;

Patent

NASA Case No.: NPO-20821-1-CU

a waveguide having a first end, a second end, and an internally reflective surface, the first end of the waveguide being attached to the second first side of the solid state emitter allowing radiant energy from the solid-state emitter to enter into the waveguide to be reflected by the internally reflective surface, the reflected radiant energy exiting at the second end of the waveguide;

a narrow angle filter comprising a microchannel to permit the passage of only unscattered radiant energy through the microchannel, the microchannel having a first end and a second end;

a beam splitting element adjacent to the second end of the waveguide and near a sample, the beam splitting element having a first side, a second side, and a third side,

wherein the first side of the beam splitting element is perpendicular to the sample and receives the reflected radiant energy from the waveguide and conducts the radiant energy to exit the second side of the beam splitting element, the second side of the beam splitting element being adjacent to a sample and directing a portion of the radiant energy to the sample and receiving some portion of the radiant energy reflected by the sample, the third side of the beam splitting element being opposite the second side of the beam splitting element and adjacent to the second end of the microchannels, the third side of the beam splitting element directing some portion of the reflected radiant energy to enter the microchannels, some portion of the radiant energy being reflected by the sample to enter the microchannel; and

a solid-state sensing element having a first side and a second side, the sensing element detecting radiant energy from the first side, the second side of the sensing element mounted to the first side of the scanning stage adjacent to the solid state emitter,

Patent

NASA Case No.: NPO-20821-1-CU

wherein that portion of the radiant energy entering the microchannel that is parallel to the microchannel walls travels to the sensing element to generate an electrical signal that can enable an image to be reconstructed by an external device.

- 16. (Original) The solid-state scanning microscope of Claim 15, wherein the beam splitting element has a polarizing filter.
- 17. (Currently Amended) A color solid-state scanning microscope, comprising:

  a scanning stage for providing structural support for moving the microscope, the scanning stage having a first side and a second side;
- a plurality of solid-state emitters for radiating energy, the wavelength of radiant energy of a predetermined number solid-state emitters is of at least two substantially different wavelengths, each emitter having a first side and a second side, the first side of each emitter radiates energy, the second side of each emitter is mounted to the first side of the scanning stage;
- a plurality of waveguides, each waveguide having a first end, a second end, and an internally reflective surface, the first end of each waveguide being attached to the second first side of a solid state emitter allowing radiant energy from the solid-state emitter to enter into the waveguide to be reflected by the internally reflective surface, the reflected radiant energy exiting at the second end of the waveguide;
- a plurality of narrow angle filters comprising a microchannel structure to permit the passage of only unscattered radiant energy through the microchannel, the microchannel having a first end and a second end;
- a plurality of beam splitting elements, each beam splitting element adjacent to the second end of the waveguide and near a sample, the beam splitting elements each having a first side, a second side, and a third side.

.08/08/2005 09:45 FAX 818 393 3160 2 007/013

Patent NASA Case No.: NPO-20821-1-CU

wherein the first side of each beam splitting element is perpendicular to

the sample and receives the reflected radiant energy from the waveguide and conducts the radiant

energy to exit the second side of the beam splitting element, the second side of the beam splitting

element being adjacent to a sample and directing a portion of the radiant energy to the sample

and receiving some portion of the radiant energy reflected by the sample, the third side of the

beam splitting element being opposite the second side of the beam splitting element and adjacent

to the second end of the microchannels, the third side of the beam splitting element directing

some portion of the reflected radiant energy to enter the microchannels, some portion of the

radiant energy being reflected by the sample to enter the microchannel; and

a plurality of solid-state sensing elements, each solid-state sensing element having

a first side and a second side, the sensing element detecting radiant energy from the first side, the

second side of the sensing element mounted to the first side of the scanning stage adjacent to the

solid state emitter,

wherein that portion of the radiant energy entering the microchannel that

is parallel to the microchannel walls travels to the sensing element to generate an electrical signal

that can enable an image to be reconstructed by an external device.

18. (Original) The color solid-state scanning microscope of Claim 17, wherein a

predetermined number of beam splitting elements have a polarizing filter.

19-21. (Canceled)